

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2020



Version number 306

Revision: 02.12.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** 600099
- **Trade name:** Coating varnish matt black E-COLL
- **Article number:** 4317784349116
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Coating material
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH  
EDE Platz 1  
D-42389 Wuppertal  
Germany  
  
Tel. +49 202 6096-0  
e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
Eye Irrit. 2 H319 Causes serious eye irritation.  
STOT SE 3 H336 May cause drowsiness or dizziness.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**  
  
GHS02 GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
acetone  
n-butyl acetate

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2020

Version number 306

Revision: 02.12.2020

**Trade name: Coating varnish matt black E-COLL**

(Contd. of page 1)

ethyl acetate

**· Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

**· Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**· 2.3 Other hazards**
**· Results of PBT and vPvB assessment**

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**· 3.2 Chemical characterisation: Mixtures**

 · **Description:** Mixture of substances listed below with nonhazardous additions.

**· Dangerous components:**

CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.12.2020

Version number 306

Revision: 02.12.2020

**Trade name: Coating varnish matt black E-COLL**

(Contd. of page 2)

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<25%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx 01-2119485493-29-0059	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	10-<25%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	1-<5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **General information:** Personal protection for the First Aider.
- **After inhalation:** Supply fresh air.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.12.2020

Version number 306

Revision: 02.12.2020

**Trade name: Coating varnish matt black E-COLL**

(Contd. of page 3)

- **Additional information** Cool endangered receptacles with water spray.

**SECTION 6: Accidental release measures****· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation

- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.

- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.

**· 6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage****· 7.1 Precautions for safe handling**

Open and handle receptacle with care.  
Use only in well ventilated areas.

- **Information about fire - and explosion protection:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.

- **Information about storage in one common storage facility:** Store away from oxidising agents.

- **Further information about storage conditions:**

Keep container tightly sealed.  
Protect from heat and direct sunlight.

- **7.3 Specific end use(s)** No further relevant information available.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.12.2020

Version number 306

Revision: 02.12.2020

**Trade name: Coating varnish matt black E-COLL**

(Contd. of page 4)

**SECTION 8: Exposure controls/personal protection****· 8.1 Control parameters****· Additional information about design of technical facilities:** No further data; see item 7.**· Ingredients with limit values that require monitoring at the workplace:****CAS: 67-64-1 acetone**IOELV Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm**CAS: 123-86-4 n-butyl acetate**IOELV Short-term value: 723 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 241 mg/m<sup>3</sup>, 50 ppm**CAS: 141-78-6 ethyl acetate**IOELV Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm  
Long-term value: 734 mg/m<sup>3</sup>, 200 ppm**· Additional information:** The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes.**· Respiratory protection:**Not necessary if room is well-ventilated.  
Use suitable respiratory protective device in case of insufficient ventilation.  
Self-contained respiratory protective device.**· Protection of hands:** Recommendation: protective gloves**· Material of gloves**Butyl rubber, BR  
Recommended thickness of the material:  $\geq 0.4$  mm**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**

Tightly sealed goggles

**· Body protection:** Protective work clothing

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.12.2020

Version number 306

Revision: 02.12.2020

**Trade name: Coating varnish matt black E-COLL**

(Contd. of page 5)

**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:****Form:**

Aerosol

**Colour:**

According to product specification

**· Odour:**

Characteristic

**· Odour threshold:**

Not determined.

**· pH-value:**

Not determined.

**· Change in condition****Melting point/freezing point:**

Undetermined.

**Initial boiling point and boiling range:** Not applicable, as aerosol.**· Flash point:**

Not applicable, as aerosol.

**· Flammability (solid, gas):**

Flammable aerosol.

**· Ignition temperature:**

415 °C

**· Decomposition temperature:**

Not determined.

**· Auto-ignition temperature:**

Product is not selfigniting.

**· Explosive properties:**

Not determined.

**· Explosion limits:****Lower:**

2.2 Vol %

**Upper:**

15 Vol %

**· Oxidising properties**

Not determined.

**· Vapour pressure at 20 °C:**

7,400 hPa

**· Density at 20 °C:**0.72 g/cm<sup>3</sup>**· Relative density**

Not determined.

**· Vapour density**

Not determined.

**· Evaporation rate**

Not applicable.

**· Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**· Partition coefficient: n-octanol/water:** Not determined.**· Viscosity:****Dynamic:**

Not determined.

Not applicable.

**Kinematic:**

Not determined.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.12.2020

Version number 306

Revision: 02.12.2020

**Trade name: Coating varnish matt black E-COLL**

(Contd. of page 6)

- **Solvent separation test:**
  - VOC (EC) % 97.13 %
  - VOC (EC) g/l 704.0 g/l
- **9.2 Other information** No further relevant information available.

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:****CAS: 106-97-8 butane, pure**

Inhalative LC50/4h 658 ppm (rat)

**CAS: 67-64-1 acetone**

Oral LD50 5,800 mg/kg (rat)

Dermal LD50 20,000 mg/kg (rabbit)

Inhalative LC50/4h 76 mg/m<sup>3</sup> (rat)**CAS: 74-98-6 propane**Inhalative LC50/4h >20 mg/m<sup>3</sup> (rat)**CAS: 123-86-4 n-butyl acetate**

Oral LD50 13,100 mg/kg (rat)

Dermal LD50 &gt;5,000 mg/kg (rabbit)

Inhalative LC50/4h &gt;21 ppm (rat)

**CAS: 141-78-6 ethyl acetate**

Oral LD50 5,620 mg/kg (rabbit)

Inhalative LC50/4h 1,600 ppm (rat)

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.12.2020

Version number 306

Revision: 02.12.2020

**Trade name: Coating varnish matt black E-COLL**

(Contd. of page 7)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****CAS: 67-64-1 acetone**

LC50/48h	8,800 mg/l (Daphnia magna)
NOEC	430 mg/l (algae)
NOEC/16h	1,700 mg/l (Pseudomonas putida)
NOEC/48h	4,740 mg/l (Pseudokirchneriella subcapitata)
96h LC50	5,540 mg/l (Oncorhynchus mykiss)

**CAS: 123-86-4 n-butyl acetate**

LC50 (96h)	18 mg/L (Pimephales promelas)
EC50 (48h)	44 mg/L (Daphnia magna)
EC50/24h	73 mg/l (Daphnia magna)
EC50/72h	647.7 mg/l (S)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.12.2020

Version number 306

Revision: 02.12.2020

**Trade name: Coating varnish matt black E-COLL**

(Contd. of page 8)

- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Harmful to aquatic organisms  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods:**  
Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste.  
Observe local regulations.

**European waste catalogue**

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

**SECTION 14: Transport information**

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** UN1950 AEROSOLS
- **IMDG, IATA** AEROSOLS

**14.3 Transport hazard class(es)**

- **ADR**



- **Class** 2 5F Gases.

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.12.2020

Version number 306

Revision: 02.12.2020

**Trade name: Coating varnish matt black E-COLL**

(Contd. of page 9)

· **Label** 2.1· **IMDG, IATA**· **Class** 2 Gases.  
· **Label** 2.1· **14.4 Packing group**  
· **ADR** Void· **14.5 Environmental hazards:**  
· **Marine pollutant:** No· **14.6 Special precautions for user** Warning: Gases.  
· **EMS Number:** F-D,S-U· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.· **Transport/Additional information:**· **ADR**  
· **Limited quantities (LQ)** 1L  
· **Transport category** 2  
· **Tunnel restriction code** D  
· **UN "Model Regulation":** UN1950, AEROSOLS, 2.1**SECTION 15: Regulatory information**

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

· **Department issuing SDS:** Product safety department· **Contact:** Head of Product Safety Department

(Contd. on page 11)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 02.12.2020

Version number 306

Revision: 02.12.2020

---

**Trade name: Coating varnish matt black E-COLL**

---

(Contd. of page 10)

**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Gas 1A: Flammable gases – Category 1A  
Aerosol 1: Aerosols – Category 1  
Press. Gas (Comp.): Gases under pressure – Compressed gas  
Flam. Liq. 2: Flammable liquids – Category 2  
Flam. Liq. 3: Flammable liquids – Category 3  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

**· \* Data compared to the previous version altered.**

---

EU

---