

Printing date 07.12.2020

Version number 305

Revision: 07.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: One-Component Multi-Primer E-COLL
- · Article number: 4317784305471
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use
- SU21 Consumer uses: Private households / general public / consumers
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Danger
- Hazard-determining components of labelling: acetone

Printing date 07.12.2020

Version number 305

Revision: 07.12.2020

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 1) n-butyl acetate butan-1-ol propan-2-ol Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H319 Causes serious eye irritation. May cause drowsiness or dizziness. H336 H411 Toxic to aquatic life with long lasting effects. · Precautionary statements If medical advice is needed, have product container or label at hand. P101 P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national/international P501 regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- EUH208 Contains reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700). May produce an allergic reaction.
- Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

	9 1		
	CAS: 115-10-6	dimethyl ether	25-50%
	EINECS: 204-065-8	🚸 Flam. Gas 1A, H220	
		🚯 Acute Tox. 2, H330	
	Reg.nr.: 01-2119472128-37-xxxx	Press. Gas (Comp.), H280	
1		(Cor	td. on page 3)

FU





Printing date 07.12.2020

Version number 305

Revision: 07.12.2020

Trade name: One-Component Multi-Primer E-COLL

	(Co	ontd. of page 2)
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	10- <25%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx 01-2119485493-29-0059	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	10- <25%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119486136-34	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	2.5-10%
CAS: 25036-25-3	Poly(Bisphenol A-co-epichlorohydrin),glycidyl end-capped Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	2.5-10%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1.25%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1.25%

 \cdot Regulation (EC) No 648/2004 on detergents / Labelling for contents less than 5 %

aromatic hydrocarbons

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Personal protection for the First Aider.
- After inhalation: Supply fresh air. Seek medical treatment in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor. (Contd. on page 4)

Printing date 07.12.2020

Version number 305

Revision: 07.12.2020

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 3)

• After swallowing: Rinse out mouth and then drink plenty of water. If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- **Protective equipment:** Do not inhale explosion gases or combustion gases. Wear self-contained respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas.





Printing date 07.12.2020

Version number 305

Revision: 07.12.2020

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 4)

Keep receptacles tightly sealed.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: Store in a cool location. Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see item 7.

 Ingredi 	ents with limit values that require monitoring at the workplace:		
CAS: 1	15-10-6 dimethyl ether		
IOELV	Long-term value: 1920 mg/m³, 1000 ppm		
CAS: 6	7-64-1 acetone		
IOELV	Long-term value: 1210 mg/m ³ , 500 ppm		
CAS: 1	CAS: 123-86-4 n-butyl acetate		
IOELV	Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm		
CAS: 1	330-20-7 xylene		
IOELV	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin		
CAS: 1	CAS: 100-41-4 ethylbenzene		
IOELV	Short-term value: 884 mg/m ³ , 200 ppm Long-term value: 442 mg/m ³ , 100 ppm Skin		

· Additional information: The lists valid during the making were used as basis.



Printing date 07.12.2020

Version number 305

Revision: 07.12.2020

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 5)

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures: Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes.

· Respiratory protection:

Not necessary if room is well-ventilated. Use suitable respiratory protective device in case of insufficient ventilation. Self-contained respiratory protective device.

· Protection of hands:



Protective gloves

Material of gloves

Butyl rubber, BR Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:	
Form:	Aerosol
Colour:	Grey
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/freezing point: 	Undetermined.



Revision: 07.12.2020

Printing date 07.12.2020

Version number 305

Trade name: One-Component Multi-Primer E-COLL

Initial boiling point and boiling range	e: Not applicable, as aerosol.	(Contd. of page 6)
· Flash point:	Not applicable, as aerosol.	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	235 °C	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Not determined.	
 Explosion limits: Lower: Upper: Oxidising properties 	1.2 Vol % 18.6 Vol % Not determined.	
· Vapour pressure at 20 °C:	4300 hPa	
· Density at 20 °C:	0.83 g/cm³	
· Relative density	Not determined.	
 Vapour density Evaporation rate 	Not determined. Not applicable.	
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.	
 Solvent separation test: Organic solvents: VOC (EC) % VOCV (CH) 	84.0 % 697,2 g/l 84,00 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 8)



Printing date 07.12.2020

Version number 305

Revision: 07.12.2020

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 7)

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
CAS: 115-	CAS: 115-10-6 dimethyl ether		
Inhalative LC50/4h 308 ppm (rat)			
CAS: 67-6	4-1 aceto	one	
Oral	LD50	5,800 mg/kg (rat)	
Dermal	LD50	20,000 mg/kg (rabbit)	
Inhalative	LC50/4h	76 mg/m³ (rat)	
CAS: 123-	₈₆₋₄ ท-bเ	ityl acetate	
Oral	LD50	13,100 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
Inhalative	LC50/4h	>21 ppm (rat)	
CAS: 7779	9-90-0 triz	zinc bis(orthophosphate)	
Oral	LD50	>5,000 mg/kg (rat)	
CAS: 1330	CAS: 1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
CAS: 71-3	CAS: 71-36-3 butan-1-ol		
Oral	LD50	790 mg/kg (rat)	
Dermal	LD50	3,400 mg/kg (rabbit)	
Inhalative	LC50/4h	8,000 ppm (rat)	

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

• Serious eye damage/irritation

Causes serious eye irritation.

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met. • **Additional toxicological information:**
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.



Printing date 07.12.2020

Version number 305

Revision: 07.12.2020

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 8)

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:			
CAS: 67-64	-1 acetone		
LC50/48h	8,800 mg/l (Daphnia magna)		
NOEC	430 mg/l (algae)		
NOEC/16h	1,700 mg/l (Pseudomonas putida)		
NOEC/48h	4,740 mg/l (Pseudokirchneriella subcapitata)		
96h LC50	96h LC50 5,540 mg/l (Oncorhynchus mykiss)		
CAS: 123-8	CAS: 123-86-4 n-butyl acetate		
LC50 (96h) 18 mg/L (Pimephales promelas)			
EC50 (48h)	EC50 (48h) 44 mg/L (Daphnia magna)		
EC50/24h	73 mg/l (Daphnia magna)		
EC50/72h	647.7 mg/l (S)		

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:

· General notes:

Harmful to aquatic organisms Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

Printing date 07.12.2020

Version number 305

Revision: 07.12.2020

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 9)

• 12.6 Other adverse effects No further relevant information available.


SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances







Printing date 07.12.2020 Version number 305 Revision: 07.12.2020
Trade name: One-Component Multi-Primer E-COLL

	(Contd. of page
· 14.5 Environmental hazards:	
· Marine pollutant:	No Sumhal (fish and toos)
· Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
 14.6 Special precautions for user 	Warning: Gases.
· EMS Number:	F-D,S-U
· 14.7 Transport in bulk according to Ann	nex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
 Limited quantities (LQ) 	1L
 Transport category 	2
 Tunnel restriction code 	D
 UN "Model Regulation": 	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Printing date 07.12.2020

Version number 305

Revision: 07.12.2020

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 11)

EU

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - oral - Category 4 Acute Tox. 2: Acute toxicity - inhalation - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

• * Data compared to the previous version altered.

