

Printing date 19.08.2020 Version number 303 Revision: 19.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600145

· Trade name: Activator Spray E-COLL

· Article number: 4317784341691

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Activator
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 Causes skin irritation. H315

STOT SE 3 May cause drowsiness or dizziness. H336

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Aquatic Chronic 2 H411

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Danger



Printing date 19.08.2020 Version number 303 Revision: 19.08.2020

Trade name: Activator Spray E-COLL

(Contd. of page 1)

· Hazard-determining components of labelling:

hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cycloalkanes, < 5% n-hexane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

Precaution	Precautionary statements					
P101	If medical advice is needed, have product container or label at hand.					
P102	Keep out of reach of children.					
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.					
P211	Do not spray on an open flame or other ignition source.					
P251	Do not pierce or burn, even after use.					
P260	Do not breathe spray.					
P271	Use only outdoors or in a well-ventilated area.					
P273	Avoid release to the environment.					
P280	Wear protective gloves/protective clothing/eye protection/face protection.					
P302+P352 IF ON SKIN: Wash with plenty of soap and water.						
P312	Call a POISON CENTER/doctor if you feel unwell.					
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.						

Dispose of contents/container in accordance with local/regional/national/international

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

P501

· Results of PBT and vPvB assessment

regulations.

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:					
CAS: 64742-49-0	hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cycloalkanes,	50-100%			
EINECS: 265-151-9	< 5% n-hexane				
Index number: 649-328-00-1	♠ Flam. Liq. 2, H225				
Reg.nr.: 01-2119475514-35-XXXX					
	Aquatic Chronic 2, H411				
	Skin Irrit. 2, H315; STOT SE 3, H336				

(Contd. on page 3)



Printing date 19.08.2020 Version number 303 Revision: 19.08.2020

Trade name: Activator Spray E-COLL

	(Coi	ntd. of page 2
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure Flam. Gas 1, H220 Press. Gas (Comp.), H280	25-50%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane The Flam. Gas 1, H220 Press. Gas (Comp.), H280	2.5-10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220 Acute Tox. 1, H330 Press. Gas (Comp.), H280	2.5-10%
CAS: 99-97-8 EINECS: 202-805-4 Index number: 612-056-00-9	N,N-dimethyl-p-toluidine → Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 → STOT RE 2, H373 Aquatic Chronic 3, H412	0.1-<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Personal protection for the First Aider. Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.



Printing date 19.08.2020 Version number 303 Revision: 19.08.2020

Trade name: Activator Spray E-COLL

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

 \cdot 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle receptacle with care. Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

(Contd. on page 5)



Printing date 19.08.2020 Version number 303 Revision: 19.08.2020

Trade name: Activator Spray E-COLL

(Contd. of page 4)

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter A/P2

· Protection of hands:



Material of gloves
 Nitrile rubber, NBR



Printing date 19.08.2020 Version number 303 Revision: 19.08.2020

Trade name: Activator Spray E-COLL

(Contd. of page 5)

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- \cdot 9.1 Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Aerosol Clear

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 365 °C

· **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Not determined.

· Explosion limits:

Lower: 1.5 Vol %
Upper: 8.5 Vol %
• Oxidising properties Not determined.

· Vapour pressure at 20 °C: 2500 hPa

· Density at 20 °C: 0.638 g/cm³

(Contd. on page 7)



Printing date 19.08.2020 Version number 303 Revision: 19.08.2020

Trade name: Activator Spray E-COLL

(Contd. of page 6)

· Relative density Not determined.

· Vapour density Not determined. · Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

Organic solvents: 99.6 % VOC (EC) % 635,7 g/l VOCV (CH) 99,64 %

· 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:							
CAS: 64742-49-0 hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cycloalkanes, < 5% n-hexane							
Oral	LD50	>5,000 mg/kg (rat)					
Dermal	LD50	>2,920 mg/kg (rat)					
		>2,000 mg/kg (rabbit)					
Inhalative	LC50/4h	>25 mg/m³ (rat)					
CAS: 106-97-8 butane, pure							
Inhalative	LC50/4h	658 ppm (rat)					
	•	(Contd. on page 8)					



Printing date 19.08.2020 Version number 303 Revision: 19.08.2020

Trade name: Activator Spray E-COLL

(Contd. of page 7)

CAS: 74-98-6 propane

Inhalative LC50/4h >20 mg/m³ (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Toxic for aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

(Contd. on page 9)



Printing date 19.08.2020 Version number 303 Revision: 19.08.2020

Trade name: Activator Spray E-COLL

(Contd. of page 8)

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

•	European	waste	cata	logue
---	----------	-------	------	-------

16 05 04* gases in pressure containers (including halons) containing hazardous substances

15 01 10* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS, ENVIRONMENTALLY

HAZARDOUS

· IMDG AEROSOLS, MARINE POLLUTANT

·IATA **AEROSOLS**

· 14.3 Transport hazard class(es)

· ADR





· Class 2 5F Gases.

· Label 2.1

· IMDG





· Class 2 Gases.

(Contd. on page 10)



Printing date 19.08.2020 Version number 303 Revision: 19.08.2020

Trade name: Activator Spray E-COLL

· Label 2.1

(Contd. of page 9)

·IATA



Class
 Label
 2 Gases.
 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: Yes

Symbol (fish and tree)
Special marking (ADR):
Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Gases.

· **EMS Number**: F-D,S-U

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

· UN "Model Regulation": UN1950, AEROSOLS, ENVIRONMENTALLY

HAZARDOUS, 2.1

SECTION 15: Regulatory information

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Methanol
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.



Printing date 19.08.2020 Version number 303 Revision: 19.08.2020

Trade name: Activator Spray E-COLL

(Contd. of page 10)

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 3: Acute toxicity - oral - Category 3

Acute Tox. 1: Acute toxicity - inhalation - Category 1

Skin Irrit. 2: Skin corrosion/irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.