

Printing date 15.12.2020 Version number 304 Revision: 15.12.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600063

· Trade name: Copper Paste Spray E-COLL

· Article number: 4317784243469

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 Causes skin irritation. H315

Asp. Tox. 1 May be fatal if swallowed and enters airways. H304 Toxic to aquatic life with long lasting effects. Aquatic Chronic 2 H411

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







· Signal word Danger

· Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light



Printing date 15.12.2020 Version number 304 Revision: 15.12.2020

Trade name: Copper Paste Spray E-COLL

(Contd. of page 1)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Causes skin irritation.

Toxic to aquatic life with long lasting effects. H411

#### · Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. P251

Use only outdoors or in a well-ventilated area. P271

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

#### · 2.3 Other hazards

#### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane  Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane  Flam. Gas 1A, H220  Acute Tox. 1, H330  Press. Gas (Comp.), H280	10-<20%
	(Cont	td. on page 3)



Printing date 15.12.2020 Version number 304 Revision: 15.12.2020

Trade name: Copper Paste Spray E-COLL

	(Cor	ntd. of page 2)
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure  Transport Flam. Gas 1A, H220  Press. Gas (Comp.), H280	5-<10%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-XXXX	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33-XXXX	Naphtha (petroleum), hydrotreated light  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
CAS: 7440-50-8 EINECS: 231-159-6 Reg.nr.: 01-2119480154-42-xxxx	copper  Acute Tox. 3, H331 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302; Eye Irrit. 2, H319	2.5-<5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Carbon dioxide



Printing date 15.12.2020 Version number 304 Revision: 15.12.2020

Trade name: Copper Paste Spray E-COLL

(Contd. of page 3)

Fire-extinguishing powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

#### · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Cool endangered receptacles with water spray.

#### **SECTION 6: Accidental release measures**

### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

### · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Open and handle receptacle with care.

Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 5)



Printing date 15.12.2020 Version number 304 Revision: 15.12.2020

Trade name: Copper Paste Spray E-COLL

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

### · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

## · Material of gloves


Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4 \text{ mm}$ 

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

## · Eye protection:





Printing date 15.12.2020 Version number 304 Revision: 15.12.2020

Trade name: Copper Paste Spray E-COLL

(Contd. of page 5)

· Body protection: Protective work clothing

#### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol

Colour: Copper colouredOdour: Petrol-likeOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gas): Flammable aerosol.

· Ignition temperature: 200 °C

• **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Not determined.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.
Oxidising properties Not determined.

· Vapour pressure: Not determined.

· Density at 20 °C: 0.66 g/cm<sup>3</sup>

· Relative density Not determined.

Vapour densityEvaporation rateNot determined.Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

**Dynamic:** Not determined.



Printing date 15.12.2020 Version number 304 Revision: 15.12.2020

Trade name: Copper Paste Spray E-COLL

(Contd. of page 6)

Kinematic: Not determined.

· Solvent separation test:

**VOC (EC)** % 71.40 % **VOC (EC) g/l** 467.4 **g/l** 

• 9.2 Other information No further relevant information available.

## **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Aldehyde

Carbon monoxide and carbon dioxide

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
CAS: 74-98-6 propane		
Inhalative	LC50/4h	>20 mg/m³ (rat)
CAS: 106-97-8 butane, pure		
Inhalative	LC50/4h	658 ppm (rat)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rat)
Inhalative	LC50/4h	20 ppm (rat)
CAS: 7440-50-8 copper		
Oral	LD50	500 mg/kg (rat)
Inhalative	LC50/4h	0.733 ppm (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.



Printing date 15.12.2020 Version number 304 Revision: 15.12.2020

Trade name: Copper Paste Spray E-COLL

(Contd. of page 7)

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 75-28-5 isobutane

EC50 (48h) 69.43 mg/L (daphnia)

- · 12.2 Persistence and degradability No further relevant information available.
- $\cdot\,\textbf{12.3 Bioaccumulative potential}\,\,\text{No further relevant information available}.$
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.



Printing date 15.12.2020 Version number 304 Revision: 15.12.2020

Trade name: Copper Paste Spray E-COLL

(Contd. of page 8)

· 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

### · 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

### · European waste catalogue

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

15 01 10\* packaging containing residues of or contaminated by hazardous substances

## **SECTION 14: Transport information**

· 14.1 UN-Number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· **ADR** UN1950 AEROSOLS, ENVIRONMENTALLY

HAZARDOUS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR





· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



• Class 2.1 • Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

· Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user

Warning: Gases.

· Hazard identification number (Kemler code):

(Contd. on page 10)



· Segregation Code

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2020 Version number 304 Revision: 15.12.2020

Trade name: Copper Paste Spray E-COLL

(Contd. of page 9)

· **EMS Number**: F-D,S-U

• Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category

C, Clear of living quarters.

SG69 For AEROSOLS with a maximum capacity of 1

litre:

Segregation as for class 9. Stow "separated from" class

1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)Excepted quantities (EQ)Code: E0

Not permitted as Excepted Quantity

Transport categoryTunnel restriction code

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E0

Not permitted as Excepted Quantity

• UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY

**HAZARDOUS** 

## **SECTION 15: Regulatory information**

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Methanol
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.



Printing date 15.12.2020 Version number 304 Revision: 15.12.2020

#### Trade name: Copper Paste Spray E-COLL

(Contd. of page 10)

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

### · Department issuing SDS: Product safety department

· Contact: Head of Product Safety Department

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 1: Acute toxicity – Category 1

Acute Tox. 3: Acute toxicity - Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

#### · \* Data compared to the previous version altered.