

Printing date 13.11.2020

Version number 306

Revision: 13.11.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier 600021
- · Trade name: Ceramic Paste Spray E-COLL
- · Article number: 4317784179591
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use
- SU21 Consumer uses: Private households / general public / consumers
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

| Aerosol 1 | H222-H229 | Extremely flammable aerosol. Pressurised container: May burst if heated. |
|-------------------|-----------|--|
| Skin Irrit. 2 | H315 | Causes skin irritation. |
| STOT SE 3 | H336 | May cause drowsiness or dizziness. |
| Asp. Tox. 1 | H304 | May be fatal if swallowed and enters airways. |
| Aquatic Chronic 3 | H412 | Harmful to aquatic life with long lasting effects. |

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger

Version number 200

Revision: 13.11.2020

Trade name: Ceramic Paste Spray E-COLL

(Contd. of page 1)

· Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Naphtha (petroleum), hydrotreated light

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves / eye protection / face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | | |
|---------------------------|----------------------------|--------------------|--|
| CAS: 74-98-6 | propane | 10-<20% | |
| EINECS: 200-827-9 | 🚸 Flam. Gas 1A, H220 | | |
| Index number: 601-003-00- | 5 Press. Gas (Comp.), H280 | | |
| Reg.nr.: 01-2119486944-21 | -XXXX | | |
| CAS: 106-97-8 | butane, pure | 10-<20% | |
| EINECS: 203-448-7 | 🚸 Flam. Gas 1A, H220 | | |
| Index number: 601-004-00- | 0 Press. Gas (Comp.), H280 | | |
| Reg.nr.: 01-2119474691-32 | -xxxx | | |
| | | (Contd. on page 3) | |



Printing date 13.11.2020

Version number 306



Printing date 13.11.2020

Version number 306

Revision: 13.11.2020

Trade name: Ceramic Paste Spray E-COLL

| | (Cor | ntd. of page 2) |
|---|--|-----------------|
| EC number: 921-024-6 Reg.nr.: 01-2119475514-35-XXXX | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% | 10-<20% |
| EC number: 927-510-4 Reg.nr.: 01-2119475515-33-XXXX | Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336 | 10-<20% |
| CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx | isobutane Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 5-<10% |
| CAS: 13463-67-7 EINECS: 236-675-5 | titanium dioxide literation dioxide | 2.5-<5% |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Personal protection for the First Aider.

· After inhalation:

Supply fresh air. Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty Headache Dizziness Coughing Disorientation Nausea

· 4.3 Indication of any immediate medical attention and special treatment needed If swallowed or in case of vomiting, danger of entering the lungs.

(Contd. on page 4)

EU -



Printing date 13.11.2020

Version number 306

Revision: 13.11.2020

Trade name: Ceramic Paste Spray E-COLL

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
 Formation of toxic gases is possible during heating or in case of fire.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation Keep away from ignition sources.
- 6.2 Environmental precautions: In case of seepage into the ground inform responsible authorities.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.



Printing date 13.11.2020

Version number 306

Revision: 13.11.2020

Trade name: Ceramic Paste Spray E-COLL

(Contd. of page 4)

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
 Observe official regulations on storing packagings with pressurised containers. Store in a cool and dry place.
- Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Protect from heat and direct sunlight.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Respiratory protection:

Respiratory protection is not required when used properly and under normal conditions. Short term filter device: Use suitable respiratory protective device in case of insufficient ventilation - filter A2 Filter A/P2

· Protection of hands:



• **Material of gloves** Nitrile rubber, NBR Penetration time (min.) : >240 min.



Printing date 13.11.2020

Version number 306

Revision: 13.11.2020

Trade name: Ceramic Paste Spray E-COLL

(Contd. of page 5)

Recommended thickness of the material: ≥ 0.7 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

| Appearance: Form: Colour: Odour: Odour: Odour threshold: | Aerosol White Petrol-like Not determined. |
|---|---|
| · pH-value: | Not determined. |
| · · Change in condition · Melting point/freezing point: · Initial boiling point and boiling range: | Undetermined. Not applicable, as aerosol. |
| · Flash point: | Not applicable, as aerosol. |
| · Flammability (solid, gas): | Not applicable. |
| · Ignition temperature: | >200 °C |
| · Decomposition temperature: | Not determined. |
| · Auto-ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Not determined. |
| Explosion limits: Lower: Upper: Oxidising properties | Not determined. Not determined. Not determined. |
| Vapour pressure: Density at 20 °C: | Not determined. 0.73 g/cm ³ |



| Printing date 13.11.2020 | Version number 306 | Revision: 13.11.2020 |
|--|------------------------------------|----------------------|
| Trade name: Ceramic Paste Spr | ay E-COLL | |
| | | (Contd. of page 6) |
| · Relative density | Not determined. | |
| Vapour density Evaporation rate | Not determined. Not applicable. | |
| Solubility in / Miscibility with water: | Not miscible or difficult to mix. | |
| · Partition coefficient: n-octan | ol/water: Not determined. | |
| · Viscositv: | | |

Not determined.

Not determined.

64.8 %

- · Dynamic:
- · Kinematic:
- · Organic solvents:
- · VOC (EC) g/l
- · 9.2 Other information

478.0 g/l No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

| CAS: 74-98-6 propane | | | |
|---|---------|-----------------------------|-------------------|
| Inhalative | LC50/4h | >20 mg/m ³ (rat) | |
| CAS: 106-97-8 butane, pure | | | |
| Inhalative | LC50/4h | 658 ppm (rat) | |
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | | | |
| Oral | LD50 | 5,000 mg/kg (rat) | |
| Dermal | LD50 | 2,000 mg/kg (rat) | |
| Inhalative | LC50/4h | 20 ppm (rat) | |
| | | | Contd. on page 8) |



Printing date 13.11.2020

Version number 306

Revision: 13.11.2020

Trade name: Ceramic Paste Spray E-COLL

| | | (Contd. of page 7) | | |
|---|----------------------------------|------------------------|--|--|
| Naphtha (petroleum), hydrotreated light | | | | |
| Oral | LD50 | 5,840 mg/kg (rat) | | |
| Dermal | LD50 | 2,920 mg/kg (rat) | | |
| Inhalative | LC50/4h | 25.2 ppm (rat) | | |
| CAS: 134 | CAS: 13463-67-7 titanium dioxide | | | |
| Oral | LD50 | >20,000 mg/kg (rat) | | |
| Dermal | LD50 | >10,000 mg/kg (rabbit) | | |
| Inhalative | LC50/4h | >6.82 ppm (rat) | | |

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity:

CAS: 75-28-5 isobutane

EC50 (48h) 69.43 mg/L (daphnia)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

(Contd. on page 9)



Printing date 13.11.2020

Version number 306

Revision: 13.11.2020

Trade name: Ceramic Paste Spray E-COLL

(Contd. of page 8)

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

15 01 04 metallic packaging

SECTION 14: Transport information

- · 14.1 UN-Number
- \cdot ADR, IMDG, IATA

- UN1950
- · 14.2 UN proper shipping name
- · ADR
- ·IMDG
- · IATA

UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR



· Label

2 5F Gases. 2.1

· IMDG, IATA





| Printing date 13.11.2020 Ver | rsion number 306 | Revision: 13.11.2020 | |
|---|--|---|--|
| Trade name: Ceramic Paste Spray E-COLL | | | |
| · Label | 2.1 | (Contd. of page 9) | |
| · 14.4 Packing group · ADR, IMDG, IATA | Void | | |
| · 14.5 Environmental hazards: | Not applicable. | | |
| 14.6 Special precautions for user Hazard identification number (Kemler code EMS Number: Stowage Code Segregation Code | Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW2 Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. | | |
| 14.7 Transport in bulk according to Annex Marpol and the IBC Code | II of Not applicable. | | |
| · Transport/Additional information: | | | |
| ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code | 1L Code: E0 Not permitted as Except 2 D | Code: E0 Not permitted as Excepted Quantity 2 | |
| IMDG Limited quantities (LQ) Excepted quantities (EQ) UN "Model Regulation": | 1L Code: E0 Not permitted as Except UN 1950 AEROSOLS, 2 | | |

SECTION 15: Regulatory information

· Directive 2012/18/EU

Named dangerous substances - ANNEX I Methanol

· Seveso category P3a FLAMMABLE AEROSOLS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 11)

— EU —



Printing date 13.11.2020

Version number 306

Revision: 13.11.2020

Trade name: Ceramic Paste Spray E-COLL

(Contd. of page 10)

· National regulations:

- Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
Contact: sdb@ede.de

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 4: Acute toxicity - dermal - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Carc. 2: Carcinogenicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\cdot * Data compared to the previous version altered.