

Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: 2-component PUR adhesive Part A

Article number: 4317784464949/A, 4317784464956/A

· UFI: 03GJ-E93G-M90W-8RF0

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Application of the substance / the mixture

Adhesives

Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer.
STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.



Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

Trade name: 2-component PUR adhesive Part A

(Contd. of page 1)

· Hazard pictograms





GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues

MDI-basiertes Polyisocyanat-Prepolymer

4,4'-methylenediphenyl diisocyanate

o-(p-isocyanatobenzyl)phenyl isocyanate

2,2'-methylenediphenyl diisocyanate

· Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P260 Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

· 2.3 Other hazards

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

(Contd. on page 3)



Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

Trade name: 2-component PUR adhesive Part A

(Contd. of page 2)

- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	25-50%
Reg.nr.: 01-2119457024-46-xxxx	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 EUH204	
	Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 %	
	Skin Irrit. 2; H315: C ≥ 5 %	
	Resp. Sens. 1; H334: C ≥ 0.1	
	STOT SE 3; H335: C ≥ 5 %	
	MDI-basiertes Polyisocyanat-Prepolymer	25-50%
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate	2.5-10%
EINECS: 202-966-0 Index number: 615-005-00-9 Reg.nr.: 01-2119457014-47-xxxx	 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 	
	EUH204	
	Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 %	
	Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1	
	Кеѕр. Зенѕ. 1, ⊓334. С ≥ 0.1 %	
	70 STOT SE 3; H335: C ≥ 5 %	
CAS: 5873-54-1	o-(p-isocyanatobenzyl)phenyl isocyanate	2.5-10%
EINECS: 227-534-9	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373	
Index number: 615-005-00-9	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;	
Reg.nr.: 01-2119480143-45xxxx	Skin Sens. 1, H317; STOT SE 3, H335 EUH204	
	Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 %	
	Skin Irrit. 2; H315: C ≥ 5 %	
	Resp. Sens. 1; H334: C ≥ 0.1	
	%	
		1



Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

Trade name: 2-component PUR adhesive Part A

	(Cont	td. of page 3)
CAS: 2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	<2.5%
EINECS: 219-784-2	♦ Eye Dam. 1, H318	
Reg.nr.: 01-2119513212-58-XXXX		
CAS: 2536-05-2	2,2'-methylenediphenyl diisocyanate	0.1-<1%
EINECS: 219-799-4		0.1-<176
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373	
Index number: 615-005-00-9	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;	
Reg.nr.: 01-21199273323-43-xxxx		
	EUH204	
	Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 %	
	Skin Irrit. 2; H315: C ≥ 5 %	
	Resp. Sens. 1; H334: C ≥ 0.1	
	%	
	STOT SE 3; H335: C ≥ 5 %	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 5)



Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

Trade name: 2-component PUR adhesive Part A

(Contd. of page 4)

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Provide floor trough without outlet.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

None.

Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 6)



Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

Trade name: 2-component PUR adhesive Part A

(Contd. of page 5)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2

· Hand protection



Protective gloves

Only use chemical-protective gloves with CE-labelling of category III.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

Value for the permeation: Level 6 / > 480 min (EN 374)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

· Colour: Brown

Odour: CharacteristicOdour threshold: Not determined.

· Melting point/freezing point: <0 °C

· Boiling point or initial boiling point and boiling

range >300 °C · Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

• Flash point: >200 °C • Ignition temperature: >400 °C

(Contd. on page 7)



Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

Trade name: 2-component PUR adhesive Part A

(Contd. of page 6)

Decomposition temperature:
 pH
 Not determined.
 Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

• Dynamic at 20 °C: 500 mPas

· Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure:
 Not determined.
 Not determined.

Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

 Important information on protection of health and environment, and on safety.

· **Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

Solvent separation test:

· VOC (EC) %
 · VOC (EC) g/I
 · VOCV (CH)
 0.00 %
 0.00 %

· Change in condition

· Softening point/range

Oxidising propertiesEvaporation rateNot determined.Not determined.

· Information with regard to physical hazard classes

 Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void · Oxidising solids Void Void Organic peroxides · Corrosive to metals Void · Desensitised explosives Void



Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

Trade name: 2-component PUR adhesive Part A

(Contd. of page 7)

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with amines.

Reacts with water and acids.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:			
CAS: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues			
Oral	LD50	10,000 mg/kg (rat) (Literatur)	
Dermal	LD50	>5,000 mg/kg (rabbit) (Literatur)	
Inhalative	LC50/4h	11 mg/m³ (rat)	
CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate			
Oral	LD50	2,200 mg/kg (mouse)	

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity

Suspected of causing cancer.

• Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 9)



Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

Trade name: 2-component PUR adhesive Part A

(Contd. of page 8)

· STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Other information (about experimental toxicology):

Persons already sensitised to isocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A).

- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

(Contd. on page 10)



Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

Trade name: 2-component PUR adhesive Part A

(Contd. of page 9)

· European	· European waste catalogue		
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS		
08 05 00	wastes not otherwise specified in 08		
08 05 01*	waste isocyanates		
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED		
15 01 00	packaging (including separately collected municipal packaging waste)		
15 01 10*	packaging containing residues of or contaminated by hazardous substances		
HP4	Irritant - skin irritation and eye damage		
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity		
HP7	Carcinogenic		
HP13	Sensitising		

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

· ADR Void · ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· UN "Model Regulation": Void

SECTION 15: Regulatory information

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Methanol
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 56a, 56b, 56c, 74

(Contd. on page 11)



Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

Trade name: 2-component PUR adhesive Part A

(Contd. of page 10)

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH204 Contains isocyanates. May produce an allergic reaction.

· Contact: sdb@ede.de

Date of previous version: 14.03.2022
Version number of previous version: 303

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic



Printing date 14.03.2022 Version number 304 (replaces version 303) Revision: 14.03.2022

Trade name: 2-component PUR adhesive Part A

(Contd. of page 11)

vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· * Data compared to the previous version altered.

EU —