

Printing date 03.12.2021 Version number 306 (replaces version 305)

Revision: 03.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier 600172
- · Trade name: High-performance cooling lubricant concentrate
- · Article number: 4317784348904, 4317784015356
- · UFI: 6R90-PG50-D20Q-12QU
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumersSU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Application of the substance / the mixture Coolant/ Cutting solution

· 1.3 Details of the supplier of the safety data sheet

 Manufacturer/Supplier: E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger



Printing date 03.12.2021

Version number 306 (replaces version 305)

Revision: 03.12.2021

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 1)

Hazard-determining components of labelling: 2-Amino-2-ethyl-1,3-propanediol polysulfides, di-tert-dodecyl Amides, C12-18 and C18-unsatd., N-(hydroxyethyl), ethoxylated 1,2-benzisothiazol-3(2H)-one			
· Precautionary sta	atements		
P101	If medical advice is needed, have product container or label at hand.		
P102	Keep out of reach of children.		
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.		
P273	Avoid release to the environment.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P302+P352 IF ON SKIN: Wash with plenty of water.			
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if			
P310	present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.		
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.		
P362+P364	Take off contaminated clothing and wash it before reuse.		
P501	Dispose of contents/container in accordance with local/regional/national/international		
	regulations.		

· Additional information:

Contains biocidal products: pyridine-2-thiol 1-oxide, sodium salt

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-53-6	baseoil - unspecified	50-100%
EINECS: 265-156-6 Index number: 649-466-00-2 Reg.nr.: 01-2119480375-34	🚸 Asp. Tox. 1, H304	
CAS: 68920-66-1 Reg.nr.: 01-2119489407-26	Fettalkohol, ethoxyliert Aquatic Chronic 2, H411 Skin Irrit. 2, H315	2.5-10%
	(Cc	ontd. on page 3)



Printing date 03.12.2021

Version number 306 (replaces version 305)

Revision: 03.12.2021

Trade name: High-performance cooling lubricant concentrate

(Cu	ontd. of page 2)
2-Amino-2-ethyl-1,3-propanediol	>1-<2.5%
📀 Eye Dam. 1, H318	
2-(2-butoxyethoxy)ethanol	>0-<2.5%
() Eye Irrit. 2, H319	
Amides, C12-18 and C18-unsatd., N-(hydroxyethyl),	>1-<2.5%
ethoxylated	
📀 Eye Dam. 1, H318	
polysulfides, di-tert-dodecyl	>1-<2.5%
() Skin Sens. 1B, H317	
1,2-benzisothiazol-3(2H)-one	<0.1%
📀 Eye Dam. 1, H318	
Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	
Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	
pyridine-2-thiol 1-oxide, sodium salt	<0.1%
Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10)	
Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit 2, H315; Eve Irrit 2, H319	
	 2-Amino-2-ethyl-1,3-propanediol Èye Dam. 1, H318 2-(2-butoxyethoxy)ethanol Èye Irrit. 2, H319 Amides, C12-18 and C18-unsatd., N-(hydroxyethyl), ethoxylated Èye Dam. 1, H318 polysulfides, di-tert-dodecyl Skin Sens. 1B, H317 1,2-benzisothiazol-3(2H)-one Èye Dam. 1, H318 Aquatic Acute 1, H400 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 % pyridine-2-thiol 1-oxide, sodium salt Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Personal protection for the First Aider.
- · After inhalation:

Supply fresh air. Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

- After swallowing: Rinse out mouth and then drink plenty of water.
 Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 4)

EU ----





Printing date 03.12.2021

Version number 306 (replaces version 305)

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fire with alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool and dry place.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store receptacle in a well ventilated area.
- · Storage class: -
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)



Printing date 03.12.2021

Version number 306 (replaces version 305)

Revision: 03.12.2021

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol		
IOELV Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm		
·DNELs		
CAS: 6892	20-66-1 Fettalkohol, ethoxylier	
Dermal	DNEL (worker)	2,080 mg/kg bw/day (professional use)
Inhalative	Long term value for employees	294 mg/m³ (professional use)
CAS: 112-	-34-5 2-(2-butoxyethoxy)ethan	ol
Oral	DNEL (populution)	1.25 mg/kg bw/day (cus)
Dermal	DNEL (worker)	20 mg/kg bw/day (professional use)
	DNEL (population)	10 mg/kg bw/day (cus)
Inhalative	Long term value for employees	34 mg/m³ (cus)
		67.5 mg/m ³ (professional use)
	DNEL (worker)	67.5 mg/m ³ (professional use)
	DNEL (population)	34 mg/m³ (cus)
· PNECs		
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol		
PNEC-Aquatic compartment Water 0.1 mg/L (Sea Water)		

• Additional information: The lists valid during the making were used as basis.

200 mg/L (S)

· 8.2 Exposure controls

PNEC-Sewage treatment plant

· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Hand protection



Protective gloves

· Material of gloves

Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm



Printing date 03.12.2021

Version number 306 (replaces version 305)

Revision: 03.12.2021

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and chemical General Information 	properties
· Colour:	According to product operification
	According to product specification
· Odour:	Characteristic
Odour threshold:	Not determined.
• Melting point/freezing point:	Undetermined.
\cdot Boiling point or initial boiling point and boiling	
range	Undetermined.
· Flammability	Not applicable.
 Lower and upper explosion limit 	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	>110 °C
Auto-ignition temperature:	Product is not selfigniting.
Decomposition temperature:	Not determined.
· pH at 20 °C	9
· Viscosity:	
 Kinematic viscosity at 40 °C 	45 mm²/s
· Kinematic: 23 °C - 4 mm (ISO 2431)	
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	0.1 hPa
· Density and/or relative density	
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
vapour density	Not determined.
9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health	Fiulu
and environment, and on safety.	
	270 °C
· Ignition temperature:	2.0 0
Explosive properties: Solvent concertion toot	Product does not present an explosion hazard.
· Solvent separation test:	
· VOC (EC) %	1-1.52 %
	(Contd. o





Printing date 03.12.2021

Version number 306 (replaces version 305)

Revision: 03.12.2021

Trade name: High-performance cooling lubricant concentrate

		(Contd. of page 6)
VOC (EC) g/l	9.1-13.9 g/l	
Change in condition		
Softening point/range	Net leteral and	
• Oxidising properties	Not determined.	
· Evaporation rate	Not determined.	
· Information with regard to physical hazard		
classes		
· Explosives	Void	
· Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
Flammable solids	Void	
 Self-reactive substances and mixtures 	Void	
 Pyrophoric liquids 	Void	
 Pyrophoric solids 	Void	
 Self-heating substances and mixtures 	Void	
 Substances and mixtures, which emit flammal 	ble	
gases in contact with water	Void	
 Oxidising liquids 	Void	
 Oxidising solids 	Void	
 Organic peroxides 	Void	
 Corrosive to metals 	Void	
 Desensitised explosives 	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 03.12.2021

Version number 306 (replaces version 305)

Revision: 03.12.2021

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 7)

· LD/LC50 values relevant for classification:			
CAS: 6474	42-53-6 ba	aseoil - unspecified	
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rat)	
CAS: 6892	CAS: 68920-66-1 Fettalkohol, ethoxyliert		
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
Inhalative	LC50/6h	>100 mg/m³ (rat)	
CAS: 112-	·34-5 2-(2·	-butoxyethoxy)ethanol	
Oral	LD50	4,900 mg/kg (rat)	
Dermal	LD50	4,900 mg/kg (rabbit)	
CAS: 381	1-73-2 ру	ridine-2-thiol 1-oxide, sodium salt	
Oral	LD50	500 mg/kg (rat)	
Dermal	LD50	1,100 mg/kg (rat)	
Inhalative	LC50/4h	1.5 ppm (rat)	

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin sensitisation May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure Based on available data, the classification criteria are not met.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
CAS: 64742-53-	6 baseoil - unspecified	
EC50 (21d)	10 mg/L (Daphnia magna)	
EC50 (48h)	>5,000 mg/L (Daphnia magna)	
NOEC (21d)	10 mg/l (Daphnia magna)	
CAS: 68920-66-1 Fettalkohol, ethoxyliert		
LC50 (96h)	108 mg/L (Brachydanio rerio)	
	(Contd on page 9)	

(Contd. on page 9) EU -



Printing date 03.12.2021

Version number 306 (replaces version 305)

Revision: 03.12.2021

Trade name: High-performance cooling lubricant concentrate

	(Contd. of page 8)
EL50 akut (48h)	51 mg/l (Daphnia magna)
EL50 akut (72h)	>100 mg/l (Desmodesmus subspicatus)
NOEC (10d)	0.16 mg/l (Lepomis macrochirus)
CAS: 112-34-5 2	2-(2-butoxyethoxy)ethanol
LC50 akut (96h)	1,300 mg/L (Lepomis macrochirus)
LC50 akut	>100 mg/L (Brachydanio rerio)
LC50	>100 mg/L (crustacean)
EC50	>100 mg/l (Desmodesmus subspicatus)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · vPvB: Not applicable.

• 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Not hazardous for water.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

SECTION 14: Transport information		
 · 14.1 UN number or ID number · ADR, IMDG, IATA 	Void	
 · 14.2 UN proper shipping name · ADR, IMDG, IATA 	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
 · 14.4 Packing group · ADR, IMDG, IATA 	Void	(Contd. on page 10)



Printing date 03.12.2021 Version number 306 (replaces version 305) Revision: 03.12.2021

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 9)

14.5 Environmental hazards:	Not applicable.		
14.6 Special precautions for user	Not applicable.		
14.7 Maritime transport in bulk according to IMO			
instruments	Not applicable.		
UN "Model Regulation":	Void		

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H322 Harmful if inhaled.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

- · Contact: sdb@ede.de
- Date of previous version: 18.10.2021
- Version number of previous version: 305

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4



Printing date 03.12.2021

Version number 306 (replaces version 305)

Revision: 03.12.2021

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 10)

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

 \cdot * Data compared to the previous version altered.

• EU —