

Printing date 26.08.2022 Version number 305 (replaces version 304)

Revision: 26.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier 600025
- · Trade name: Semi-Fluid Grease Spray E-COLL
- · Article number: 4317784251198
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use
- SU21 Consumer uses: Private households / general public / consumers
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	9 Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2	H315	Causes skin irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Aquatic Chronic 2	2 H411	Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Danger
- Hazard-determining components of labelling: pentane



Printing date 26.08.2022

Version number 305 (replaces version 304)

Revision: 26.08.2022

Trade name: Semi-Fluid Grease Spray E-COLL

(Contd. of page 1)

Hydrocarbons, C6, isoalkanes, <5% n-hexane Naphtha (petroleum), hydrotreated light (Benzene < 0.1%)

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

Bangereae compensition		
CAS: 75-28-5	isobutane	10-25%
EINECS: 200-857-2	📀 Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119485395-27-xxxx		
CAS: 109-66-0	pentane	10-25%
EINECS: 203-692-4	🚸 Flam. Liq. 2, H225	
Index number: 601-006-00-1	🚯 Asp. Tox. 1, H304	
Reg.nr.: 01-2119459286-30-xxxx	Aquatic Chronic 2, H411	
	Acute Tox. 4, H302; STOT SE 3, H336	
	EUH066	
	(Conto	d. on page 3)

EU -



Printing date 26.08.2022

Version number 305 (replaces version 304)

Revision: 26.08.2022

Trade name: Semi-Fluid Grease Spray E-COLL

	(Con	td. of page 2)
CAS: 74-98-6	propane	10-25%
EINECS: 200-827-9	🚸 Flam. Gas 1A, H220	
Index number: 601-003-00-5	🚸 Acute Tox. 1, H330	
Reg.nr.: 01-2119486944-21-xxxx	Press. Gas (Comp.), H280	
CAS: 106-97-8	butane, pure	10-25%
EINECS: 203-448-7	🚸 Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119474691-32-xxxx		
EC number: 931-254-9	Hydrocarbons, C6, isoalkanes, <5% n-hexane	10-25%
Reg.nr.: 01-2119484651-34	🛞 Flam. Liq. 2, H225	
	🚯 Asp. Tox. 1, H304	
	🚯 Aquatic Chronic 2, H411	
	🚯 Skin Irrit. 2, H315; STOT SE 3, H336	
EC number: 926-605-8	Naphtha (petroleum), hydrotreated light (Benzene < 0.1%)	2.5-10%
Reg.nr.: 01-2119786291-36-xxx	🚸 Flam. Liq. 2, H225	
	🚯 Asp. Tox. 1, H304	
	🚯 Aquatic Chronic 2, H411	
	🚯 STOT SE 3, H336	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Personal protection for the First Aider. Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air. Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water. Seek immediate medical advice.

- \cdot 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 4)



Printing date 26.08.2022

Version number 305 (replaces version 304)

Revision: 26.08.2022

Trade name: Semi-Fluid Grease Spray E-COLL

(Contd. of page 3)

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- **5.2 Special hazards arising from the substance or mixture** In case of fire, the following can be released: Carbon monoxide (CO)

· 5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases. Wear self-contained respiratory protective device.

· Additional information

Cool endangered receptacles with water spray. Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Use only in well ventilated areas. Store in cool, dry place in tightly closed receptacles. Keep away from heat and direct sunlight.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges. Do not spray onto a naked flame or any incandescent material.



Printing date 26.08.2022

Version number 305 (replaces version 304)

Revision: 26.08.2022

Trade name: Semi-Fluid Grease Spray E-COLL

(Contd. of page 4) Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- **Requirements to be met by storerooms and receptacles:** Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Store away from oxidising agents. Store away from foodstuffs.
- Further information about storage conditions: Store under lock and key and out of the reach of children.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 109-66-0 pentane

IOELV Long-term value: 3000 mg/m³, 1000 ppm

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Immediately remove all soiled and contaminated clothing Keep away from foodstuffs, beverages and feed.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation. Short term filter device: Filter A/P2

· Hand protection



Protective gloves

• Material of gloves Nitrile rubber, NBR



Printing date 26.08.2022

Version number 305 (replaces version 304)

Revision: 26.08.2022

Trade name: Semi-Fluid Grease Spray E-COLL

(Contd. of page 5)

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and chemical p General Information 	properties	
	Colourlage	
· Colour:	Colourless	
· Odour:	Characteristic	
Odour threshold:	Not determined.	
Melting point/freezing point:	Undetermined.	
· Boiling point or initial boiling point and boiling	_	
range	>34 °C	
· Flammability	Not applicable.	
 Lower and upper explosion limit 		
· Lower:	1.5 Vol %	
· Upper:	10.9 Vol %	
Flash point:	Not applicable, as aerosol.	
Ignition temperature:	365 °C	
· Decomposition temperature:	Not determined.	
· pH	Not determined.	
· Viscosity:		
· Kinematic viscosity	Not determined.	
· Kinematic: 23 °C - 4 mm (ISO 2431)		
· Dynamic:	Not determined.	
· Solubility		
· water:	Not miscible or difficult to mix.	
· Partition coefficient n-octanol/water (log value)	Not determined.	
Vapour pressure at 20 °C:	8,300 hPa	
• Density and/or relative density	0,500 HF a	
· Density:	Not determined.	
•		
· Relative density	Not determined.	
· Vapour density	Not determined.	
· 9.2 Other information		
Appearance: Form:	Aaroool	
· FVIIII.	Aerosol	(Contd. on page 7)
		EU



Printing date 26.08.2022

Version number 305 (replaces version 304)

Revision: 26.08.2022

Trade name: Semi-Fluid Grease Spray E-COLL

	(Contd. of page 6)
Important information on protection of health	
and environment, and on safety.	
 Auto-ignition temperature: 	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
	Danger of bursting when heated > 50°C. Formation of
	explosive gas or vapour/air mixtures possible if the
	container is damaged and through use.
Solvent separation test:	44.0.04
· Organic solvents:	41.2 %
· VOC (EC) %	<59.63 %
· VOC (EC) g/l	596.3 g/l
· Change in condition	
· Softening point/range	
· Oxidising properties	Not determined.
· Evaporation rate	Not applicable.
· Information with regard to physical hazard	
classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Volu
Extremely flammable aerosol. Pressurised containe	er: May burst if heated
 Oxidising gases 	Void
 Gases under pressure 	Void
· Flammable liquids	Void
 Flammable solids 	Void
 Self-reactive substances and mixtures 	Void
 Pyrophoric liquids 	Void
 Pyrophoric solids 	Void
 Self-heating substances and mixtures 	Void
· Substances and mixtures, which emit flammab	le
gases in contact with water	Void
· Oxidising liquids	Void
 Oxidising solids 	Void
 Organic peroxides 	Void
 Corrosive to metals 	Void
 Desensitised explosives 	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- · 10.4 Conditions to avoid No further relevant information available.



Printing date 26.08.2022

Version number 305 (replaces version 304)

Revision: 26.08.2022

Trade name: Semi-Fluid Grease Spray E-COLL

(Contd. of page 7)

• **10.5 Incompatible materials:** No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
CAS: 109-66-0 pentane		
Oral	LD50	2,000 mg/kg (rat)
Dermal	LD50	3,000 mg/kg (rab)
Inhalative	LC50/4h	364 mg/m³ (rat)
CAS: 74-98-6 propane		
Inhalative	LC50/4h	>20 mg/m³ (rat)
CAS: 106-97-8 butane, pure		
Inhalative	LC50/4h	658 ppm (rat)

· Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- Endocrine disrupting properties None of the ingredients is listed.

(Contd. on page 9)

EU



Printing date 26.08.2022

Version number 305 (replaces version 304)

Revision: 26.08.2022

Trade name: Semi-Fluid Grease Spray E-COLL

(Contd. of page 8)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 75-28-5 isobutane

EC50 (48h) 69.43 mg/L (daphnia)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

• 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
 14.2 UN proper shipping name ADR IMDG IATA 	Void AEROSOLS, MARINE POLLUTANT AEROSOLS



Printing date 26.08.2022 Version number 305 (replaces version 304) Revision: 26.08.2022

Trade name: Semi-Fluid Grease Spray E-COLL

(Contd. of page 9) · 14.3 Transport hazard class(es) · ADR · Class 2 5F Gases. · Label 2.1 · IMDG · Class 2 Gases. Label 2.1 · IATA · Class 2 Gases. · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree) · 14.6 Special precautions for user Warning: Gases. · EMS Number: F-D,S-U · 14.7 Maritime transport in bulk according to IMO Not applicable. instruments Transport/Additional information: · ADR · Limited quantities (LQ) 1L · Transport category 2 · Tunnel restriction code D · UN "Model Regulation": Void

SECTION 15: Regulatory information

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 26.08.2022

Version number 305 (replaces version 304)

Revision: 26.08.2022

Trade name: Semi-Fluid Grease Spray E-COLL

(Contd. of page 10)

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

pentane

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Naphtha (petroleum), hydrotreated light (Benzene < 0.1%)

Hazard statements

- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I Methanol
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H330 Fatal if inhaled.

EU

E-COLL

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 305 (replaces version 304)

Revision: 26.08.2022

Trade name: Semi-Fluid Grease Spray E-COLL

(Contd. of page 11) H336 May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. H411 EUH066 Repeated exposure may cause skin dryness or cracking. · Department issuing SDS: Product safety department · Contact: sdb@ede.de Date of previous version: 26.08.2022 · Version number of previous version: 304 · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 1: Acute toxicity – Category 1 Skin Irrit. 2: Skin corrosion/irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

·* Data compared to the previous version altered.