

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** 600137
- **Trade name:** Rust primer, reddish brown E-COLL
- **Article number:** 4317784305327, 4317784305303
- **UFI:** FHGQ-FARE-5A0V-Q7RP
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 - SU19 Building and construction work
 - SU21 Consumer uses: Private households / general public / consumers
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Application of the substance / the mixture** Anticorrosion additive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 - E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH
 - EDE Platz 1
 - D-42389 Wuppertal
 - Germany

Tel. +49 202 6096-0
e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226	Flammable liquid and vapour.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

2.2 Label elements

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

Trade name: Rust primer, reddish brown E-COLL

(Contd. of page 1)

· Hazard pictograms

GHS02 GHS07 GHS09

· Signal word Warning**· Hazard-determining components of labelling:**Hydrocarbons, C9, aromatics
Reaction mass of ethylbenzene and xylene
1-methoxy-2-propanol
cobalt(II) 2-ethylhexanoate**· Hazard statements**H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.**· Precautionary statements**P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
P391 Collect spillage.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.**· Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

*** SECTION 3: Composition/information on ingredients****· 3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

Trade name: Rust primer, reddish brown E-COLL

(Contd. of page 2)

· Dangerous components:		
CAS: 64742-95-6 EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H335-H336 EUH066	10-50%
EC number: 905-588-0 Reg.nr.: 01-2119539452-40 02-2119752448216-32	Reaction mass of ethylbenzene and xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-10%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-<5%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6	trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	>2.5-<5%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35-xxxx	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	>1-5%
CAS: 13939-25-8 EINECS: 237-714-9	aluminium dihydrogen triphosphate ⚠ Eye Irrit. 2, H319	0-10%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	cobalt(II) 2-ethylhexanoate ⚠ Repr. 1B, H360 ⚠ Aquatic Acute 1, H400 ⚠ Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin Sens. 1A, H317 Aquatic Chronic 3, H412	0-<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Personal protection for the First Aider.
Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air.
Seek medical treatment in case of complaints.
In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

Trade name: Rust primer, reddish brown E-COLL

(Contd. of page 3)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*** SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

Trade name: Rust primer, reddish brown E-COLL

(Contd. of page 4)

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.
Protect from heat.**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**Store only in the original receptacle.
Provide floor trough without outlet.**Information about storage in one common storage facility:** Store away from oxidising agents.**Further information about storage conditions:** Keep container tightly sealed.**Storage class:** -**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 107-98-2 1-methoxy-2-propanol**

IOELV	Short-term value: 568 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
	Skin

Additional information: The lists valid during the making were used as basis.**8.2 Exposure controls****Appropriate engineering controls** No further data; see item 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**Avoid contact with the eyes and skin.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Do not eat or drink while working.**Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation - filter A2

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

Trade name: Rust primer, reddish brown E-COLL

(Contd. of page 5)

· Hand protection

Protective gloves

· Material of gloves

Nitrile rubber, NBR

Penetration time (min.) : >480 min.

Recommended thickness of the material: ≥ 0.4 mm**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Recommendation: safety glasses with side protection shield**· Body protection:** Use protective suit.**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information**

- **Colour:** Red-brown
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** >100 °C
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** Not determined.
- **Upper:** Not determined.
- **Flash point:** 24 °C (Reaction mass of ethylbenzene and xylene)
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity at 20 °C** 200 s (DIN 53211/4)
- **Kinematic: 23 °C - 4 mm (ISO 2431)**
- **Dynamic:** Not determined.
- **Solubility**
- **water:** Not miscible or difficult to mix.
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure at 20 °C:** 6.7-8.2 hPa (Reaction mass of ethylbenzene and xylene)
- **Density and/or relative density**
- **Density at 20 °C:** 1.41 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

Trade name: Rust primer, reddish brown E-COLL

(Contd. of page 6)

· 9.2 Other information**· Appearance:****· Form:**

Fluid

· Important information on protection of health and environment, and on safety.**· Ignition temperature:**

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Solvent separation test:**· Organic solvents:**

10.1-12.3 %

· VOC (EC) g/l

430.0 g/l

· Solids content:

6-10 %

· Change in condition**· Drip point:****· Oxidising properties**

Not determined.

· Evaporation rate

Not determined.

· Information with regard to physical hazard classes**· Explosives**

Void

· Flammable gases

Void

· Aerosols

Void

· Oxidising gases

Void

· Gases under pressure

Void

· Flammable liquids

Flammable liquid and vapour.

· Flammable solids

Void

· Self-reactive substances and mixtures

Void

· Pyrophoric liquids

Void

· Pyrophoric solids

Void

· Self-heating substances and mixtures

Void

· Substances and mixtures, which emit flammable gases in contact with water

Void

· Oxidising liquids

Void

· Oxidising solids

Void

· Organic peroxides

Void

· Corrosive to metals

Void

· Desensitised explosives

Void

SECTION 10: Stability and reactivity**· 10.1 Reactivity** No further relevant information available.**· 10.2 Chemical stability****· Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.**· 10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

Trade name: Rust primer, reddish brown E-COLL

(Contd. of page 7)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

CAS: 1314-13-2 zinc oxide

Oral LD50 >5,000 mg/kg (rat)

CAS: 7779-90-0 trizinc bis(orthophosphate)

Oral LD50 >5,000 mg/kg (rat)

CAS: 107-98-2 1-methoxy-2-propanol

Oral LD50 5,660 mg/kg (rat)

Dermal LD50 13,000 mg/kg (rabbit)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

Trade name: Rust primer, reddish brown E-COLL

(Contd. of page 8)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods:**
Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste.
Observe local regulations.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR** UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS
- **IMDG, IATA** PAINT
- **14.3 Transport hazard class(es)**
- **ADR**
- **Class** 3 (F1) Flammable liquids.



(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

Trade name: Rust primer, reddish brown E-COLL

(Contd. of page 9)

· Label 3

· IMDG

· Class 3 Flammable liquids.
· Label 3

· IATA

· Class 3 Flammable liquids.
· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA III

· 14.5 Environmental hazards:

· Marine pollutant:

· Special marking (ADR):

Product contains environmentally hazardous substances: Solvent naphtha (petroleum), light arom.
No
Symbol (fish and tree)
Symbol (fish and tree)

· 14.6 Special precautions for user

· Hazard identification number (Kemler code):

· EMS Number:

· Stowage Category

Warning: Flammable liquids.
30
F-E, S-E
A

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

· Excepted quantities (EQ)

5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· Transport category

· Tunnel restriction code

3
D/E

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ)

5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
UN 1263 PAINT, 3, III, ENVIRONMENTALLY
HAZARDOUS

· UN "Model Regulation":

EU

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

Trade name: Rust primer, reddish brown E-COLL

(Contd. of page 10)

SECTION 15: Regulatory information

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS09

· **Signal word** Warning

· **Hazard-determining components of labelling:**

Hydrocarbons, C9, aromatics

Reaction mass of ethylbenzene and xylene

1-methoxy-2-propanol

cobalt(II) 2-ethylhexanoate

· **Hazard statements**

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 308 (replaces version 307)

Revision: 13.03.2023

Trade name: Rust primer, reddish brown E-COLL

(Contd. of page 11)

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360 May damage fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department**· Contact:** Head of Product Safety Department**· Date of previous version:** 01.12.2020**· Version number of previous version:** 307**· Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A
- Repr. 1B: Reproductive toxicity – Category 1B
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.